



CLEAN ACROSS AMERICA AND
THROUGHOUT THE WORLD™

ZEP MANUFACTURING COMPANY
P.O. BOX 2015
ATLANTA, GEORGIA 30301

12/16/93

ISSUE DATE: 06/14/93

SUPERSEDES: 11/03/92

HAZARD IDENTIFICATION AND DISPOSAL INFORMATION

SECTION I - EMERGENCY CONTACTS

TELEPHONE:

(404) 352-1680

BETWEEN 8:00 AM - 5:00 PM (EST)

MEDICAL EMERGENCY:

(404) 435-2973

(404) 432-2873

(404) 424-4789

(404) 319-6151

(404) 242-3561

NON-OFFICE HOURS, WEEKENDS
AND HOLIDAYS, PLEASE CALL YOUR
LOCAL POISON CONTROL

TRANSPORTATION EMERGENCY:

(404) 922-0823

CHEMTREC:

1-800-424-9300

TOLL-FREE - ALL CALLS RECORDED

DISTRICT OF COLUMBIA:

(202) 483-7616

ALL CALLS RECORDED

SECTION II - HAZARDOUS INGREDIENTS

DESIGNATIONS

* HYDROTREATED LIGHT PETROLEUM DISTILLATES * paraffinic, naphthenic solvent; CAS# 64742-47-8; RTECS#
None; Supplier suggested PEL- 100 ppm/ 525 mg/m3

TLV
(PPM)
ND

EFFECTS
(SEE REVERSE)
CBL IRR

% IN
PROD
> 90

SECTION III - HEALTH HAZARD DATA

Special Note: MSDS data pertains to the product as dispensed from the container. Adverse health effects would not be expected under recommended conditions of use (diluted) so long as prescribed safety precautions are practiced.

Acute Effects of Overexposure:

Overexposure to the vapors from this product may produce mucous membrane irritation, particularly of the eye and respiratory tract. Overexposure to vapors may also produce mild central nervous system depression characterized by headache, dizziness, nausea, and stupor, leading to unconsciousness in extreme cases. Introduction of solvents, as in aspiration of vomitus fluid, may produce chemical pneumonia. Existing respiratory disorders and lung diseases may be aggravated by inhalation of vapors.

Chronic Effects of Overexposure:

Skin which is repeatedly defatted by contact with this product may be more susceptible to irritation, infection, or dermatitis. None of the hazardous ingredients are listed as carcinogens by IARC, NTP, & OSHA

Est'd PEL/TLV: 100 ppm

Primary Routes of Entry: Inh.

HMIS Codes: HEALTH 2; FLAM. 2; REACT. 0; PERS. PROTECT. 8; CHRONIC HAZ. YES

FIRST AID PROCEDURES:

Skin: Wash contaminated skin thoroughly with soap or a mild detergent. Apply a skin cream with lanolin. Get medical attention if irritation persists.
Eyes: Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting upper and lower lids. Get medical attention at once.
Inhale: Move exposed person to fresh air. If irritation persists, get medical attention promptly.
Ingest: If swallowed, do not induce vomiting. If vomiting occurs, keep head below hip level. Get emergency medical attention immediately.

SECTION IV - SPECIAL PROTECTION INFORMATION

Protective Clothing: Wear neoprene, nitrile, or natural rubber gloves or gloves with proven resistance to the ingredients listed.
Eye Protection: Wear tight-fitting splash-proof safety glasses especially if contact lenses are worn.
Respiratory Protection: When exposure levels exceed PEL/TLV (likely in confined areas) use an organic vapor respirator (eg Zep 2211).
Ventilation: Provide local exhaust/ventilation as needed to keep concentration of vapors below exposure limits (PEL/TLV).

SECTION V - PHYSICAL DATA

Boiling Point (°F):	413-458	Specific Gravity:	0.811	Vapor Pressure (mmHg):	0.9 @ 77F
Percent Volatile by Volume (%):	100	Vapor Density (air=1):	N/D	Evaporation Rate (N/D = 1):	N/D
Solubility in Water:	INSOLUBLE	pH (concentrate):	N/A	pH (use dilution of):	N/A

Appearance and Odor: A water white, oily liquid with a hydrocarbon odor.

SECTION VI - FIRE AND EXPLOSION DATA

Flash Point (°F) (method used): 170F (TCO)
Flammable Limits: LEL 0.8% UEL 6.0%
Extinguishing Media: Carbon dioxide, dry chemical, water fog, and alcohol foam.
Special Fire Fighting: Wear self-contained positive pres. breathing apparatus.
Unusual Fire Hazards: Fire exposed drums should be cooled with stream of water.

USEPA SF



1288519

ZEP MANUFACTURING COMPANY MATERIAL SAFETY DATA SHEET PAGE 2

SECTION VII - REACTIVITY DATA

Stability: Stable
 Incompatibility (avoid): Heat, open flame, spark, and oxidizing agents.
 Polymerization: Will not occur.
 Hazardous Decomposition: Carbon dioxide, carbon monoxide, and other unidentified organic compounds.

SECTION VIII - SPILL AND DISPOSAL PROCEDURES

Steps to be Taken in Case Material is Released or Spilled:

Immediately eliminate all flame, ignition and high-heat sources. Absorb spill on inert absorbent material (eg Zap-o-zorb). Pick up and place residue in a suitable container for disposal. Wash area thoroughly with a detergent solution and rinse well with water.

Waste Disposal Method:

Liquid wastes are not permitted in landfills. Product is not considered a hazardous waste under RCRA. Unusable liquid may be absorbed on an inert absorbent material (eg Zap-O-Zorb), drummed, and taken to a chemical or industrial landfill. Pretreatment may be required before landfilling. Consult local, state, or federal agencies for proper disposal in your area.

RCRA Hazardous Waste Numbers: N/A

SECTION IX - SPECIAL PRECAUTIONS

Precautions to be Taken When Handling and Storing:

Combustible! Store and use away from heat, sparks, open flame, or any source of ignition. Post "No Smoking" signs according to local regulations for combustible liquids. Keep product away from skin and eyes. Do not breathe spray mists or vapors. Clothing or shoes which become contaminated with substance should be removed promptly and not worn until thoroughly cleaned. Store tightly closed container in a dry area at temps. between 40-120 degrees F. Keep out of the reach of children.

SECTION X - TRANSPORTATION DATA

DOT Proper Shipping Name: NONE

DOT Hazard Class: N/A

DOT I.D. Number: N/A

EPA TSCA Chemical Inventory: ALL INGREDIENTS ARE LISTED

EPA CWA 40CFR Part 117 substance (RQ in a single container): N/A

DOT Label/Placard: NONE

NOTICE

Thank you for your interest in, and use of, Zep products. Zep Manufacturing Co. is pleased to be of service to you by supplying this Material Safety Data Sheet for your files. Zep Manufacturing is concerned for your health and safety. Zep products can be used safely with proper protective equipment and proper handling practices consistent with label instructions and the MSDS. Before using any Zep product, be sure to read the complete label and the Material Safety Data Sheet.

As a further word of caution, Zep wishes to advise that serious accidents have resulted from the misuse of empty containers. "Empty" containers retain residue liquid and/or vapor and can be dangerous. DO NOT pressure, cut, weld, braze, solder, drill, grind or expose such containers to heat, flame, or other sources of ignition; they may explode or develop harmful vapors and possibly cause injury or death. Clean empty containers by triple rinsing with water or an appropriate solvent. Empty containers must be sent to a drum reconditioner before reuse.

TERMS AND ABBREVIATIONS USED IN THE MSDS:
BY SECTION ALPHABETICALLY

SECTION II: HAZARDOUS INGREDIENTS

CA: Carcinogen - A chemical listed by the National Toxicology Program (NTP), the International Agency for Research on Cancer (IARC) or OSHA as a definite or possible human cancer causing agent.

AS #: Chemical Abstract Services Registry Number - A universally accepted numbering system for chemical substances.

BL: Combustible - At temperatures between 100°F and 600°F chemical gives off enough vapor to ignite if a source of ignition is present as tested with a closed cup tester.

NS: Central Nervous System depressant reduces the activity of the brain and spinal cord.

OR: Corrosive - Causes irreversible alterations in living tissue (e.g. burns).

ES: ESIGNATIONS; Chemical and common names of hazardous ingredients.

IR: Eye Irritant Only - Causes reversible reddening and/or inflammation of eye tissues.

EXPOSURE LIMITS: The time weighted average (TWA) airborne concentration at which most workers can be exposed without any expected adverse effects. Primary sources include ACGIH TLVs and OSHA PEL's (TWA, STEL and ceiling mits).

ACGIH: American Conference of Governmental Industrial Hygienists.

CEILING: The concentration that should not be exceeded in the workplace during any part of the working exposure.

OSHA: Occupational Safety and Health Administration

PEL: Permissible Exposure Limit - A set of time weighted average exposure values, established by OSHA, for a normal 8-hour day and a 40-hour work week.

PPM: Parts per million - unit of measure for exposure limits.

(S) SKIN: Skin contact with substance can contribute to overall exposure.

STEL: Short Term Exposure Limit - Maximum concentration

for a continuous 15-minute exposure period.

TLV: Threshold Limit Value - A set of time weighted average exposure limits, established by the ACGIH, for a normal 8-hour day and a 40-hour work week.

FBI: Flammable - At temperatures under 100°F, chemical gives off enough vapor to ignite if a source of ignition is present as tested with a closed cup tester.

HAZARDOUS INGREDIENTS: Chemical substances determined to be potential health or physical hazards by the criteria established in the OSHA Hazard Communication Standard - 29 CFR 1910.1200.

HTX: Highly toxic - The probable lethal dose for 70 kg (150 lb.) man and may be approximated as less than 6 teaspoons (2 tablespoons).

IRR: Irritant - Causes reversible effects in living tissues (e.g. inflammation) - primarily skin and eyes.

NA: Not Applicable - Category is not appropriate for this product.

ND: Not Determined - Insufficient information for a determination for this item.

RTECS #: Registry of Toxic Effects of Chemical Substances - an unreviewed listing of published toxicology data on chemical substances.

SARA: Superfund Amendments and Reauthorization Act - Section 313 designates chemicals for possible reporting for the Toxic Release Inventory.

SEN: Sensitizer - Causes allergic reaction after repeated exposure.

TOX: Toxic - The probable lethal dose for a 70 kg (150 lb.) man is one ounce (2 tablespoons) or more.

SECTION III: HEALTH HAZARD DATA

ACUTE EFFECT: An adverse effect on the human body from a single exposure with symptoms developing almost immediately after exposure or within a relatively short time.

CHRONIC EFFECT: Adverse effects that are most likely to occur from repeated exposure over a long period of time.

ESTD PEL/TLV: This estimated, time-weighted average, exposure limit, developed by using a formula provided by the ACGIH, pertains to airborne concentrations from the product as a whole. This value should serve as guide for providing safe workplace conditions to nearly all workers.

HMS CODES: Hazardous Material Identification System - a rating system developed by the National Paint and Coating Association for estimating the hazard potential of a chemical under normal workplace conditions. These risk estimates are indicated by a numerical rating given in each of three hazard areas (Health/Flammability/Reactivity) ranging from a low of zero to a high of 4. A chronic hazard is indicated with a yes. Consult HMIS training guides for Personal Protection letter codes which indicate necessary protective equipment.

PRIMARY ROUTE OF ENTRY: The way one or more hazardous ingredients may enter the body and cause a generalized systemic or specific-organ toxic effect.

ING: Ingestion - A primary route of exposure through swallowing of material.

INH: Inhalation - A primary route of exposure through breathing of vapors.

SKIN: A primary route of exposure through contact with

the skin.

SECTION IV: SPECIAL PROTECTION INFORMATION

Where respiratory protection is recommended, use only MSHA and NIOSH approved respirators and dust masks.

MSHA: Mine Safety and Health Administration

NIOSH: National Institute for Occupational Safety and Health.

SECTION V: PHYSICAL DATA

EVAPORATION RATE: It refers to the rate of change from the liquid state to the vapor state at ambient temperature and pressure in comparison to a given substance (e.g. water).

pH: A value representing the acidity or alkalinity of an aqueous solution (Acidic pH = 1; Neutral pH = 7; Alkaline pH = 14).

PERCENT VOLATILE: The percentage of the product (liquid or solid) that will evaporate at 212°F and ambient pressure.

SOLUBILITY IN WATER: A description of the ability of the product to dissolve in water.

SECTION VII: REACTIVITY DATA

HAZARDOUS DECOMPOSITION: Breakdown products expected to be produced upon product decomposition or fire.

INCOMPATIBILITY: Material contact and conditions to avoid to prevent hazardous reactions.

POLYMERIZATION: Indicates the tendency of the product's molecules to combine in a chemical reaction releasing excess pressure and heat.

STABILITY: Indicates the susceptibility of the product to spontaneously and dangerously decompose.

SECTION VIII: SPILL AND DISPOSAL PROCEDURES

RCRA WASTE NOS: RCRA (Resource Conservation and Recovery Act) waste codes (40 CFR 261) applicable to the disposal of spilled or unusable product from the original container.

SECTION X: TRANSPORTATION DATA

CWA: Clean Water Act

RQ: Reportable Quantity - The amount of the specific ingredient that, when spilled to the ground and can enter a storm sewer or natural watershed, must be reported to the National Response Center, and other regulatory agencies.

TSCA: Toxic Substances Control Act - a federal law requiring all commercial chemical substances to appear on an inventory maintained by the EPA.

DISCLAIMER

All statements, technical information and recommendations contained herein are based on available scientific tests or data which we believe to be reliable. The accuracy and completeness of such data are not warranted or guaranteed. We cannot anticipate all conditions under which this information and our products, or the products of other manufacturers in combination with our products, may be used. Zep assumes no liability or responsibility for loss or damage resulting from the improper use or handling of our products, from incompatible product combinations, or from the failure to follow instructions, warnings, and advisories in the product's label and Material Safety Data Sheet.